

- Bright Color 2.4" TFT LCD Display
- Durable, Compact and Lightweight
- Accurate, Reliable Readings During Low Perfusion and Motion
- Audible/Visual Alarms with Adjustable Alarm Limits
- Can Be Used for Spot-Check and Continuous Monitoring
- Maximum Data Storage for 100 Patients; 72-hour Trend Data for Each Patient.
- Suitable for Adult, Pediatric and Neonate





SpO₂:

Measurement Range: 0~100%

±2% during 70%~100% Accuracy:

0%~69% unspecified

Pulse Rate:

Measurement Range: 30 bpm ~ 250 bpm Accuracy: 1 bpm or $\pm 2\%$

take the bigger one

EtCO2

Measurement Range: 0~150mmHg

Resolution: 0.1mmHg (0~69)mmHg

0.25mmHg (70~150)mmHg

(0~40)mmHg ±2 mmHg Accuracy:

 $\pm 5\%$ (41~70)mmHg (71~100)mmHg $\pm 8\%$ $\pm 10\%$ (101~150)mmHg

Repiration Rate:

Measurement Range: 2~150BPM Accuracy: ± 1 BPM

Alarm:

Audible and Visual Alarms for High/Low SpO2 and Pulse

Alarm Limits Adjustable

Alarm Silence Interval: 30, 60, 90 and 120 sec.

Low Perfusion Warning Indicator Sensor Disconnect Alarm

Low-battery Warning Indicator

Audio Indicators:

Sensor off (every 30 seconds)

Pulse Beep Key-pressing Low Battery

Power Requirements:

Four Standard "AA" Size Batteries Battery Capacity: ≥12 hours

Environment:

Operating Temperature: 0°C~50°C (32°F ~122°F)

Humidity: ≤95%

Altitude: -390m~5,000m (-1,280 ft ~16,404 ft)

Transport/Storage Temperature: -40°C~70°C (-40°F ~158°F)

Humidity: ≤95%

Physical Characteristics:

Dimensions: 69mm (W) x130mm (H) x 22mm (D) [2.72in (W) x 5.11in (H) x 0.87in (D)]

195g/100g (with batteries/without batteries) Gross Weight: 495g/395g (with batteries/without batteries)

Compliance:

1.SpO₂: ISO 9919: 2005

2. Safety Standards:

EN60601-1: 1990+A1: 1993+A2: 1995+A13: 1996

Type BF-Applied

3. Alarm: IEC60601-1-8: 2005

4. EMC: EN60601-1-2: 2001, Group 1 Class A

5. Environment: WEEE (2002/96/EC)

Option: Memory and Data Output, CO2

Available SpO2 Sensors and CO2 Sensors:



Adult/Pediatric Finger



Adult/Pediatric Soft-Finger



Single Patient Disposable



Mainstream CO₂



Sidestream CO2



Nasal Cannula

NEWTECH, INC.

R1-B1, Hi-Tech Industrial Park, Nanshan District, Shenzhen 518057 CHINA Tel: 86-755 26525910 Fax: 86-755 26525386