


MaxBlend™

- Vital help for new neonatal resuscitation guidelines
- Available in both high and low flow
- 24 month overall warranty
- Compact size
- Low Maintenance
- Easy calibration



Maximize your workspace with MaxBlend™ air/oxygen mixer:

The MaxBlend™ is the only oxygen/air blender with a built-in monitor designed with you in mind, to consolidate limited workspace in making oxygen delivery clean and simple. Maxtec® uses the leading technology in blending and combines it with state-of-the-art monitoring.

Specifications

Model Weight:	4.5 lbs (approximately)
Display Range:	0 - 100% Oxygen
Display Resolution:	0.1% Oxygen
Flow Range:	0 - 30 lpm (low flow), 2 - 100 lpm (high flow)
Operating Temperature:	15°C - 40°C
Accuracy and Linearity:	± 2% of Full Scale at constant temperature, RH and pressure when calibrated at full scale ± 3% Actual Oxygen level over full operating temperature range
Response Time:	90% of final value in approximately 15 seconds at 23°C
Power Requirements:	2 AA Alkaline batteries
Battery Life:	3000 hours (continuous operation, no alarming)
High and Low Alarm:	15% - 99% (low flow), 18% - 99% (high flow)

Part Numbers

MaxBlend™ (low flow)	R203P05-001	MaxBlend™ (high flow)	R204P05-001
--------------------------------	-------------	---------------------------------	-------------